


Vita Twist II Surface Mount Downlight



Ensured by low glare system



Honeycomb Louvre Colour 10



COB LED

Specification :



- Luminaire Power Consumption : 20W
- Lumen Output : 1200lm
- Input Voltage : 36V
- Color Temperature : 3000/4000K
- Dimmable Options : Dali / 0-10V / Push / Phase
- CRI : >90
- Dimension : Dia 110 x H140mm
- Beam Angle : 40°
- Construction & Finish : die-cast AL powder-coated in white and black
- Weight : 650g
- Lifetime : 50,000 hours (LM-80)
- Compliance : CE
- 3-year Warranty



Features :

- Optional honeycomb
- Low glare design
- COB LED

UGR
S = 0.250



Room/Dimensions	ViewedCrosswise				ViewedEndwise					
x=2H y=2H	18.9	19.8	19.1	19.8	20.0	18.9	19.8	19.1	19.8	20.0
x=2H y=3H	19.1	19.8	19.4	20.0	20.2	19.1	19.8	19.4	20.0	20.2
x=2H y=4H	19.2	19.8	19.5	20.1	20.3	19.2	19.8	19.5	20.1	20.3
x=2H y=6H	19.3	19.9	19.6	20.1	20.4	19.3	19.9	19.6	20.1	20.4
x=2H y=8H	19.4	19.9	19.7	20.2	20.5	19.4	19.9	19.7	20.2	20.5
x=2H y=12H	19.5	20.0	19.9	20.3	20.6	19.5	20.0	19.9	20.3	20.6
x=4H y=2H	18.9	19.6	19.2	19.8	20.1	18.9	19.6	19.2	19.8	20.1
x=4H y=3H	19.3	19.8	19.6	20.1	20.4	19.3	19.8	19.6	20.1	20.4
x=4H y=4H	19.5	19.9	19.9	20.3	20.6	19.5	19.9	19.9	20.3	20.6
x=4H y=6H	19.7	20.0	20.1	20.4	20.8	19.7	20.0	20.1	20.4	20.8
x=4H y=8H	19.8	20.1	20.2	20.5	20.9	19.8	20.1	20.2	20.5	20.9
x=4H y=12H	20.1	20.4	20.5	20.8	21.2	20.1	20.4	20.5	20.8	21.2
x=6H y=4H	19.5	19.8	19.9	20.2	20.6	19.5	19.8	19.9	20.2	20.6
x=6H y=6H	19.8	20.0	20.2	20.5	20.9	19.8	20.0	20.2	20.5	20.9
x=6H y=8H	20.0	20.3	20.5	20.7	21.2	20.0	20.3	20.5	20.7	21.2
x=6H y=12H	20.4	20.6	20.9	21.1	21.6	20.4	20.6	20.9	21.1	21.6
x=12H y=4H	19.5	19.8	19.9	20.2	20.6	19.5	19.8	19.9	20.2	20.6
x=12H y=6H	19.8	20.0	20.3	20.5	20.9	19.8	20.0	20.3	20.5	20.9
x=12H y=8H	20.1	20.3	20.6	20.8	21.3	20.1	20.3	20.6	20.8	21.3